

CONSTRUCTION

Fiber system	100% BCF Polypropylene	
Construction	Pattern scroll loop	
Backing system	DuraBac Modular	
Pile weight	20 oz./y ²	680 g/m ²
Pile height	0.19"	5 mm
Gauge	1/12	47.2 rows/10 cm
Stitches	10 s.p.i.	39.4 stitches/10 cm
Density	6000	10.4 kilotex/cm ²

SUSTAINABILITY

CRI/CCI air quality test	Green Label Plus Certified
Environmental awareness	Eligible for any recycling program
Recycled Content	Durabac Modular backing - min. 20% pre-consumer, 100% PVC Free

CLASS - I FIRE RATING / PERFORMANCE

Flammability	Radiant Panel ASTM E648 - Class I (direct glue) Methenamine Pill - DOC FF 1-70 - passes Smoke Density ASTM E662 - < 450 (flaming mode)
Static generation	3.0 kV or less (AATCC 134)
Colorfastness to light	5.0 (AATCC 16)

INSTALLATION

Modular size (w x l)	19.7" x 19.7"	50 cm x 50 cm
Packaging	20 tiles/carton 38 lbs/carton 32 cartons/pallet	6 y ² /carton
Recommended adhesive	HENRY'S H-630 PreachPro	
Installation method	Monolithic, Quarter-Turn, Ashlar and Brick	

QUICK SHIP

Homecrest Carpet Tiles are in stock and ready to ship from our Grand Rapids, MI warehouse.

STYLE 7193 COLORS

01 Monroe 03 Calder 04 Bridge 07 Lyon 09 Campau

10 YEAR WARRANTY

Seriously Stain Proof - Spills can be easily removed through gentle blotting allowing your carpet to remain beautiful in spite of life's little mishaps. Our Backing Performance warranty guarantees that the backing on this product will not shrink, grow, cup or dome, which ensures easy installation and product longevity.

Commercial Wear Warranty - The natural characteristics of geometric or linear patterns in carpet tile can result in double-dark or double-light lines at the seam and to some degree a pattern run-off or bias. This is not a manufacturing defect. These characteristics should always be taken into consideration when choosing the installation method of a modular carpet. While select styles are offered in both modular and broadloom formats, they are not an exact match since the equipment used in the manufacturing of both patterns are entirely different. *Percentages of recycled content are accurate at date of printing. The availability of these inputs may fluctuate. Refer to homecrestflooring.com for the most current specifications.

