



## CROSWELL OAK FLOORING SPECIFICATION INFORMATION



Come home to the distinct unique look of hardwood with the added benefit of scratch resistance, via a UV cured urethane aluminum oxide finish. The beauty of hardwood flooring lies in the natural variation of the material. Since each tree is different, each installation will be unique. Homecrest Hardwood flooring is available in several shades & textures, constructed of multiply layers of engineered hardwood from various species of wood ranging from exotic Acacia to beautiful European Oak. Installation is up to you as it can be either glued, nailed, stapled or floated.

### PRODUCT INFORMATION & CONSTRUCTION

Brand	Homecrest Hardwood
Collection	Croswell Oak
Product Category	Engineered Flooring
Overall Thickness:	1/2"
Board Width	5", 7 1/2" Mixed width
Board Length	Random length up to 82"
Surface Texture	Kerf saw marked & Matte wire brushed
Top Veneer Thickness	2 mm
Wear Layer	UV cured urethane with scratch resistant aluminum oxide
Construction	Multi-layer crossply wood veneers with four-sided bevel profile
Available Installation Methods	Your choice installation: Glue, Nail, Staple, Float
Approved Locations	Below, At or Above grade level
Radiant Heat Approved	Yes, installs over all In-floor heating systems
Warranty	50 Year Residential 5 Year Light Commercial
Packaging	28.66sf/ctn; 137.68 sf/pallet
Weight	48.06 lbs/ctn; 2306.88 lbs/pallet

### SELLING FEATURES

- High quality, high design value oriented wood flooring line.
- Most mainstream Midwest visuals and species.
- UV Cured Urethane with Aluminum Oxide Finish – provides a finish that will last a lifetime.
- Matte Wire Brushed Finish with Chiseled edges, various kerf & skip sawn marks feature prominently in this distinct line.



[homecrestflooring.com](http://homecrestflooring.com)



PRODUCT CERTIFIED FOR LOW CHEMICAL EMISSIONS  
UL.COM/GG  
UL 2818