



QUINCY HICKORY FLOORING SPECIFICATION INFORMATION

Come home to the distinct unique look of hardwood with the added benefit of scratch resistance, via a UV cured urethane aluminum oxide finish. The beauty of hardwood flooring lies in the natural variation of the material. Since each tree is different, each installation will be unique. Homecrest Hardwood flooring is available in several shades & textures, constructed of multiply layers of engineered hardwood from various species of wood ranging from exotic Acacia to beautiful European Oak. Installation is up to you as it can be either glued, nailed, stapled or floated.



Kempstead

PRODUCT INFORMATION & CONSTRUCTION

Brand	Homecrest Hardwood
Collection	Quincy Hickory
Product Category	Engineered Flooring
Overall Thickness:	1/2"
Board Width	6 1/2"
Board Length	Random length up to 72"
Surface Texture	Matte wire brushed
Top Veneer Thickness	2 mm
Wear Layer	UV cured urethane with scratch resistant aluminum oxide
Construction	Multi-layer crossply wood veneers with four-sided bevel profile
Available Installation Methods	Your choice installation: Glue, Nail, Staple, Float
Approved Locations	Below, At or Above grade level
Radiant Heat Approved	Yes, installs over all In-floor heating systems
Warranty	50 Year Residential 5 Year Light Commercial
Packaging	38.99sf/ctn; 1520.61 sf/pallet
Weight	64.64 lbs/ctn; 2520.96 lbs/pallet

SELLING FEATURES

- High quality, high design value oriented wood flooring line.
- Most mainstream Midwest visuals and species.
- UV Cured Urethane with Aluminum Oxide Finish – provides a finish that will last a lifetime.
- Gorgeous Matte Wire Brushed Hickory textured visuals give this line a nostalgic weathered look.



homecrestflooring.com



PRODUCT CERTIFIED FOR
LOW CHEMICAL EMISSIONS
UL.COM/GG
UL 2818