

COORDINATING MOLDINGS

for



Cascade Ridge WATERPROOF FLOORING

Technical Information

Slim Trim

LVT Transition/Reducer with track
3-in-1: Reducer, T-Molding, & End Cap



VersaEdge Extra Tall

Stair Nose – 1.5" Height



Moisture Proof Quarter Round



Versatrack

For Flooring 1/4-3/8" (6-9.5 mm)
Optional Use with Reducer, T-Molding, & End Cap



Versatrack Shim

Used with Versatrack End Cap For Flooring 4.5 - 9.5 mm



Slim Cap




All Moldings are 94" Long

SlimTrim

Functions as a Reducer, T-Molding, and End Cap.

Surface Material: High Wear Resistant Aluminum Oxide Laminate

Core Material: PVC




VersaEdge Extra Tall

The VersaEdge Stair Nose combines style and function to enhance the beauty of a staircase or step. For use on flooring with an overall thickness of up to 0.75" (19 mm).

Surface Material: High Wear Resistant Aluminum Oxide Laminate


Core Material: Aluminum



VERSAEDGE APPLICATIONS

"Lock-Down" Install (e.g. Stair Treads)

Laminate/Vinyl/Hardwood/Engineered Wood
Vinyl/LVT Alternative Flush



Flooring Planks Must Be Glued!

"Floating" Install

Laminate/Engineered Wood
Vinyl/LVT




Slim Cap

Slim Cap is used to transition from vinyl to carpet, masonry (fireplaces), sliding doors and other exterior door jambs.

Surface Material: High Wear Resistance Aluminum Oxide Laminate


Core Material: PVC



SlimTrack



Included with Slim Cap

Material: Cold Roll Steel.



Versatrack Shim

Included with Slim Cap




Quarter Round (Standard or Moisture Proof)

Quarter Rounds are used to conceal the required expansion space between the wall and the flooring. Comes as standard MDF or moisture proof.

Surface Material:

Core Material: Quarter Round: Standard MDF.

Moisture Proof Quarter Round: Exterior Grade Composite Wood Product



FOR MORE DETAILED INSTALLATION INFORMATION, TIPS, AND ADVICE GO TO: INSTALLATIONADVICE.COM