



homecrestflooring.com



Charleston



MISSION POINT **PLUS** LUXURY VINYL FLOORING

Homecrest Mission Point + is a loose lay luxury vinyl flooring product ideal for residential, multi family and commercial applications. On a mission to offer premium style and high performance flooring, we present Mission Point + Luxury Vinyl.

PRODUCT INFORMATION & CONSTRUCTION

Collection Information	Mission Point +
Brand	Homecrest Flooring
Product Type	Luxury Vinyl Plank
Dimensions	Plank: 7" x 48" x 5mm nominal Tile: 18" x 18" x 5mm nominal
Packaging	23.33 sf/ctn; 10 pcs, 39.3 lbs 22.50 sf/ctn; 10 pcs, 39.1 lbs
Overall Gauge	5mm (.197")
Wear Layer	20 mil
Finish	Ceramic Reinforced Urethane
Texture	All Over Embossing
Installation	Loose lay with perimeter glue or full spread
Radiant Heat Approved	Yes

SELLING FEATURES

- Your choice installation for ease
- Minimal subfloor prep
- Comfortable underfoot
- Waterproof, stain resistant & worry-free
- Low maintenance floor
- Replace single planks as needed

TESTING

Test Item	Standard	Minimum Requirement Result
Product Classification	ASTM F1700	Class III, Type B Solid Vinyl Tile
Size Tolerance	ASTM F2421	± 0.016 in/lin. ft Passes
Thickness Tolerance	ASTM F386	± 0.005 in Passes
Wear Layer Thickness Tolerance	ASTM F410	0.020" min Passes
Squareness	ASTM F2421	0.010" max Passes
Dimensional Stability	ASTM F2199	0.020 in/lin. ft. max Passes
Slip Resistance	ASTM D2047	Dry 0.63, Wet 0.73
Residual Indentation	ASTM F1914	Avg. < 8% Passes
Static Load Limit	ASTM F970	> 250 PSI Passes
Resistance to Light	ASTM F1515	ΔE < 8 avg. max Passes
Chemical Resistance	ASTM F925	No more than slight change Passes
Resistance to Heat	ASTM F1514	ΔE < 8 avg. max Passes
Curling After Exposure to Heat	ISO 23999	≤ 2 Passes
Smoke Density	ASTM E662	≤ 450 Passes
Flexibility	ASTM F137	≤ 1.0" (No cracks or breaks) Passes