



homecrestflooring.com



Charleston



# MISSION POINT **PLUS** LUXURY VINYL FLOORING

Homecrest Mission Point + is a loose lay luxury vinyl flooring product ideal for residential, multi family and commercial applications. On a mission to offer premium style and high performance flooring, we present Mission Point + Luxury Vinyl.

## PRODUCT INFORMATION & CONSTRUCTION

Collection Information	Mission Point +
Brand	Homecrest Flooring
Product Type	Luxury Vinyl Plank
Dimensions	Plank: 7" x 48" x 5mm nominal Tile: 18" x 18" x 5mm nominal
Packaging	23.33 sf/ctn; 10 pcs, 39.3 lbs 22.50 sf/ctn; 10 pcs, 39.1 lbs
Overall Gauge	5mm (.197")
Wear Layer	20 mil
Finish	Ceramic Reinforced Urethane
Texture	All Over Embossing
Installation	Loose lay with perimeter glue or full spread
Radiant Heat Approved	Yes

## SELLING FEATURES

- Your choice installation for ease
- Minimal subfloor prep
- Comfortable underfoot
- Waterproof, stain resistant & worry-free
- Low maintenance floor
- Replace single planks as needed

## TESTING

Test Item	Standard	Minimum Requirement   Result
Product Classification	ASTM F1700	Class III, Type B Solid Vinyl Tile
Size Tolerance	ASTM F2421	± 0.016 in/lin. ft   Passes
Thickness Tolerance	ASTM F386	± 0.005 in   Passes
Wear Layer Thickness Tolerance	ASTM F410	0.020" min   Passes
Squareness	ASTM F2421	0.010" max   Passes
Dimensional Stability	ASTM F2199	0.020 in/lin. ft. max   Passes
Slip Resistance	ASTM D2047	Dry 0.63, Wet 0.73
Residual Indentation	ASTM F1914	Avg. < 8%   Passes
Static Load Limit	ASTM F970	> 250 PSI   Passes
Resistance to Light	ASTM F1515	ΔE < 8 avg. max   Passes
Chemical Resistance	ASTM F925	No more than slight change   Passes
Resistance to Heat	ASTM F1514	ΔE < 8 avg. max   Passes
Curling After Exposure to Heat	ISO 23999	≤ 2   Passes
Smoke Density	ASTM E662	≤ 450   Passes
Flexibility	ASTM F137	≤ 1.0" (No cracks or breaks)   Passes