



## BALDWIN HICKORY FLOORING SPECIFICATION INFORMATION



Come home to the distinct unique look of hardwood with the added benefit of scratch resistance, via a UV cured urethane aluminum oxide finish. The beauty of hardwood flooring lies in the natural variation of the material. Since each tree is unique, each installation will be unique. Homecrest Hardwood flooring is available in several shades & textures, constructed of multi-layered engineered hardwood in species like Hickory and White Oak. Installation is up to you as it can be either glued, nailed, stapled or floated.

### PRODUCT INFORMATION & CONSTRUCTION

Collection Information	Baldwin Hickory
Brand	Homecrest Hardwood
Species	Hickory
Product Type	Multi-ply engineered Tongue & groove profile 3mm sliced face top veneer
Edge Profile	Four-sided micro bevel
Plank Size	9/16" x 7.5" Random length up to 75.75"
Packaging	30.92 sf/ctn; 1236.8 sf/pallet
Weight	69 lbs/ctn; 2760 lbs/pallet
Wear Layer	Matte urethane finish, UV cured with scratch resistant aluminum oxide
Surface Texture	Wirebrushed
Installation	Your choice installation: Glue, nail, staple, float
Approved Locations	Installs below, at or above grade level
Warranty	50 year finish Lifetime structural warranty

### SELLING FEATURES

- High quality, high design valued oriented wood flooring line
- Most mainstream Midwest visuals and species
- UV Cured Aluminum Oxide Finish – provides a finish that will last a lifetime.
- Handscraped and hand sculpted visuals help mask the imperfections, scratches, dents, debris, etc. caused by everyday life.



homecrestflooring.com



CERTIFIED BY  
SCS Global Services